



ARP A-Fence

GATE

Our aluminium gates offer an ideal solution for adding privacy and easy access to outdoor areas like balconies, terraces, and garden spaces. Designed to integrate seamlessly with the A-Fence system. These gates bring a modern, cohesive look to your property. Constructed from durable, powder-coated aluminium, they are built to last and require minimal maintenance, making them a smart choice for entrances and storage areas.

MADE IN® BRITAIN


A2-s1, d0 A2fl-s1 FIRE RATED

Specification Datasheet





Dimensions





Benefits include:

- 30 year guarantee
- A2-s1, d0 Fire Rated
- 1100mm width between post
- Simple fixing for hassle free installation
- Modular system
- Available in Textured Anthracite Grey 7016 or Jet Black 9005



ARP A-Fence


FENCE PANELS


Specification Datasheet A2-s1, d0


PROFILE OPTIONS A2fl-s1

SLATTED OPTION

A choice of 5 profile options allows you to make your divider or fencing solutions unique with all options interchangeable. Giving you complete flexibility in your design.







Benefits include:

- 30 year guarantee
- A2-s1, d0 Fire Rated
- 1.8m span between posts
- Simple fixing for hassle free installation
- Modular system
- Available in Textured Anthracite Grey 7016 or Jet Black 9005



240mm Interlocking Slats

Product Specification

- Fire resistant: A2-s1, d0
- Coating thickness 60-80 microns
- Impact test with an energy of 2.5kN to ensure that the coating adheres to the substrate to EN ISO 6272 / ASTM D2794
- Bend test on 5mm mandrel to ensure adhesion after bending to EN ISO 1519
- Machu Test (accelerated corrosion test) in a solution made up of sodium chloride acetic acid and hydrogen peroxide at 37 °C Duration 48 hours
- Qualicoat 2.4.1. cross hatch cuts are made at 2mm spacings with one being at 90 degrees to the other cut, tape is the applied left for 2 minutes and removed to check for adhesion of paint (EN ISO 2409 2013)
- Qualicoat 2.18 sawing and drilling test to ensure no flaking after cutting (using sharp tools)
- Acid salt spray test ISO 9227
- EN ISO 3231 Resistance to humid atmospheres containing Sulphur Dioxide
- EN ISO 11341 Accelerated weathering test
- EN ISO 20810 Natural weathering test (Florida Test) (Carried out on Powder Type)
- EN ISO 12206-1 Resistance to mortar (Carried out on powder type)
- EN ISO 6270 2 Constant climate condensation water test.

Protective Finish

The A-Fence is coloured using the Qualicoat powder coating finish. Qualicoat is a quality label organisation committed to maintaining and promoting the quality of coating on aluminium and its alloys for architectural applications.

Installation

A-Fences simple fixing system with minimal parts allows for speedy installation on-site.

Construction

The A-Fence is constructed completely from 100% aluminium (6063 T6 grade), up to 67% of which has been recycled to make these joists eco-friendly and much better for the environment

Maintenance

Due to the fact that AliRail is aluminium and finished using the 7 stage Qualicoat system, little or no maintenance is required. General grime can be removed simply with a damp, lint-free cloth or mop with warm soapy water.

Colour Options

Available finishes include our 2 standard colours, (RAL 7016 & 9005) all in a sleek powder-coat, providing a range of aesthetically pleasing options to suit any property.







JET BLACK RAL 9005

Warranty

The A-Fence is supplied with a **30 year warranty** against splitting, cracking, warping, splintering, rotting, twisting and material or manufacturing defects. It has a minimum **60 year life** expectancy.





A2-s1, d0 & A2fl-s1



ALL ALUMINIUM



HEAT RESISTAN



QUICK AND EAS TO INSTALL



LOW MAINTENANCE



RECYCLABLE



STABLE IN ALI WEATHER CONDITIONS