

ARP SYSTEM EXTRAS




Discover the ultimate decking perfection with ARP's comprehensive range of accessories, each designed for unmatched durability, style, and functionality to elevate any outdoor space.


Benefits include:

- Long-lasting durability and weather resistance
- Enhances aesthetic appeal of outdoor spaces
- Meets UK safety and fire standards
- Quick and easy installation process
- Sustainable, recyclable aluminium materials
- Versatile for various outdoor applications

1. ANGLE TRIM



Colour-matched to your decking this unique tapered 3 metre angle trim is 30mm x 20mm and can be used in either orientation, providing a simple yet versatile option for finishing the board edges. Ideal to reduce trip hazards.



3. SPREADER PLATES



This simple aluminium plate is used to spread the imposed load of the ARP decking system when installing to your sub-structure.




3. SELF DRILLING SCREWS



Our self-drilling screws are designed for quick and easy installation, offering a secure and durable fixing solution.

4. FIRE RESISTANT TAPE



Fire-Resistant tape is a great non-combustible solution for preventing vibrations between the Spreader Plate and Pedestal Brackets

Product Specification

- Fire resistant: A2-s1, d0 and A2fl-s1, A1 when mill finished
- Coating thickness - 60-80 microns
- Impact test - with an energy of 2.5kJ to ensure that the coating adheres to the substrate to EN ISO 6272 / ASTM D2794
- Bend test - on 5mm mandrel to ensure adhesion after bending to EN ISO 1519
- Machu Test (accelerated corrosion test) - in a solution made up of sodium chloride acetic acid and hydrogen peroxide at 37 °C Duration 48 hours
- Qualicoat 2.4.1. - cross hatch cuts are made at 2mm spacings with one being at 90 degrees to the other cut, tape is applied left for 2 minutes and removed to check for adhesion of paint (EN ISO 2409 2013)
- Qualicoat 2.18 - sawing and drilling test to ensure no flaking after cutting (using sharp tools)
- Acid salt spray test - ISO 9227
- EN ISO 3231 - Resistance to humid atmospheres containing Sulphur Dioxide
- EN ISO 11341 - Accelerated weathering test
- EN ISO 20810 - Natural weathering test (Florida Test) (Carried out on Powder Type)
- EN ISO 12206-1 - Resistance to mortar (Carried out on powder type)
- EN ISO 6270 – 2 - Constant climate condensation water test.

Construction

Many of our ARP accessories are constructed completely from 100% aluminium (6063 T6 grade), up to 67% of which has been recycled to make these accessories eco-friendly and much better for the environment.

Colour Options

The ARP Angle Trims are available in 2 standard colours - RAL 7016 Anthracite Grey & RAL 8014 Sepia Brown.



Warranty

All our accessories are supplied with a **30 year warranty** against splitting, cracking, warping, splintering, rotting, twisting and material or manufacturing defects. It has a minimum **60 year life expectancy**.

Protective Finish

ARP accessories are coloured using the Qualicoat powder coating finish. Qualicoat is a quality label organisation committed to maintaining and promoting the quality of coating on aluminium and its alloys for architectural applications.



HEAT
RESISTANT



QUICK AND EASY
TO INSTALL



LOW
MAINTENANCE



RECYCLABLE



STABLE IN ALL
WEATHER
CONDITIONS

Email: info@aratedproducts.co.uk
www.aratedproducts.co.uk

ARP
A-RATED PRODUCTS